
Technical data sheet

Equipotential busbar for small systems

Item number: 5015502







- Sealable/labellable
- Base plate made of strip galvanised steel
- Contact strip and screws made of nickel-plated brass

Connection options:

- 3 x multi-core cables to 6 mm²
- 2 x multi-core cables to 16 mm²

Fluor



Brass

Master data

Item number	5015502
Description 1	Equipotential busbar
Description 2	for small systems
Manufacturer	OBO
Dimension	72x45mm
Colour	Grey
Material	Brass
Smallest sales unit	1
Unit of quantity	Piece
Weight	9 kg
Weight unit	kg/100 pc.


Technical data sheet

Equipotential busbar for small systems






Dimensions



•	72 mm
Width	43.5 mm
Height	29 mm



Technical data

Quantity of flat conductor connections up to 30 mm	0
Quantity of flat conductor connections up to 40 mm	0
Quantity of cable connections up to 16 mm², rigid	2
Quantity of cable connections up to 25 mm², rigid	0
Quantity of cable connections up to 6 mm², rigid	3
Quantity of cable connections up to 95 mm², rigid	0
Quantity of round conductor connections 10 mm	0
Quantity of round conductor connections 8 mm	0
Quantity of round conductor connections 8-10 mm	0
Quantity of round conductor connections, total	0
Version for	With cover hood
Type	Fixed structure
Insulator	no
Surface of the terminal	Nickel-plated
Surface of the contact rail	Nickel-plated
Material of the terminal	Brass
Material of the contact rail	Brass