

# Technical data sheet

## Clamp clip 2056 H-foot 1-fold, plastic pressure sleeve, Al

Item number: 1186436



Clamp clip with hammerhead foot, plastic pressure sleeve made of polypropylene. For vertical and horizontal mounting of 1 single cable on a C-profile rail. For a slot width 16–17 mm. With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. We recommend the use of a counter-sleeve.



**Alu** Aluminium

### Master data

|                                   |                         |
|-----------------------------------|-------------------------|
| Item number                       | 1186436                 |
| Type                              | BS-H1-K-40 ALU          |
| Description 1                     | Clamp clip 2056         |
| Manufacturer                      | OBO                     |
| Dimension                         | 34-40mm                 |
| Material                          | Aluminium               |
| Smallest sales unit               | 100                     |
| Unit of quantity                  | Piece                   |
| Weight                            | 2.7 kg                  |
| Weight unit                       | kg/100 pc.              |
| CO Footprint (GWP) Cradle-to-Gate | 0,3378 kg COe / 1 Piece |


# Technical data sheet

Clamp clip 2056 H-foot 1-fold, plastic pressure sleeve, Al

Item number: 1186436



## Dimensions



|                  |         |
|------------------|---------|
| Length           | 22.5 mm |
| Width            | 45 mm   |
| Height           | 74 mm   |
| Plate thickness  | 2 mm    |
| Dimension A      | 22.5 mm |
| Dimension B      | 45 mm   |
| Dimension C      | 34 mm   |
| Dimension G (mm) | M6      |
| Dimension H      | 74 mm   |
| Dimension L      | 47 mm   |
| Dimension t      | 2 mm    |

## Technical data

|                                                |               |
|------------------------------------------------|---------------|
| Number of cables/pipes                         | 1             |
| For pipe diameter, max.                        | 40 mm         |
| For pipe diameter, min.                        | 34 mm         |
| for rail with slot width (with interval), max. | 17 mm         |
| for rail with slot width (with interval), min. | 16 mm         |
| Thread                                         | M6            |
| Halogen-free                                   | yes           |
| Length of external dimensions                  | 34 mm         |
| Max. Tightening torque                         | 2 Nm          |
| With plastic trough                            | yes           |
| Mounting type                                  | Profile rail  |
| Slot width                                     | 10 mm         |
| Clamping range D, max.                         | 40 mm         |
| Clamping range D, min.                         | 34 mm         |
| Surface addition                               | Untreated     |
| Material addition                              | Aluminium     |
| With counter-trough                            | no            |
| Material of trough                             | Plastic       |
| Material quality of trough                     | Polypropylene |