

# Technical data sheet

## Cable tray SKS 60 A4

Item number: 6056750



SKS 60 = Heavy-duty cable tray system with 60 mm side height.  
The cable tray, type SKS, should also be used for maintenance of electrical function. For additional data, please refer to BSS fire protection systems. The cable tray is fastened to the bracket with bolts, type FRS M6 x 12.  
Magnetic shield insulation without cover 20 dB, with cover 50 dB.



**A4** Stainless steel

**2B** Bright, treated

### Master data

Item number	6056750
Description 1	Cable tray SKS
Description 2	perforated
Manufacturer	OBO
Dimension	60x100x3000
Material	Stainless steel
Surface	Bright, treated
Surface standard	
Smallest sales unit	3
Unit of quantity	Metre
Weight	260 kg
Weight unit	kg/100 m


# Technical data sheet

## Cable tray SKS 60 A4

Item number: 6056750



### Dimensions



Length	3,000 mm
Length	10 ft
Width	100 mm
Width	4 in
Height	60 mm
Height	2 in
Plate thickness	0.06 in
Plate thickness	1.5 mm
Dimension B	100 mm

### Technical data

Connector version	Without connectors
Mounting system fastening type	Floor Ceiling Wall
Walkable	no
Maintain electrical functions	yes
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Usable cross-section	58 cm <sup>2</sup>
Usable cross-section	5800 mm <sup>2</sup>
Rustproof steel, pickled	no
Side perforation	yes
Wide-span version	no
Load test type according to IEC 61537	Type II
Type of connector, cable support system	Screwed

# Technical data sheet

## Cable tray SKS 60 A4

Item number: 6056750



### Loads

Insertable support spacings, min.	1.5 m
Insertable support spacings, max.	3 m
Support spacing 1.5 m	2.65 kN/m
Support spacing 2.0 m	1.8 kN/m
Support spacing 2.5 m	1.15 kN/m
Support spacing 3.0 m	0.5 kN/m

