

Technical data sheet

FineController FC-B for sockets B/F

Item no. 5092840



Type 3 surge protection device to EN 61643-11 designed for use on protective contact sockets of the B/F country version.



- Adapter
- Disconnection device and function display
- With increased touch protection



Master data

Item no.	5092840
Type	FC-B/F
Description 1	FineController
Dimension	230V
Colour	Pure white
RAL number	9010
Smallest sales unit (VG)	1 Piece
Weight	7,90 kg/100 pc.

Technical data



SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Response time	<25 ns
Max. continuous operating voltage	275,00 V
Country-specific version	B/F
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	3 kA
Rated current	16,00 A
Nominal voltage	230,00 V
Installation type	Adapter
Maximum discharge current (8/20 μs)	8,00 kA
Maximum back-up fuse	16,00 A
With interference suppression filter	<input type="checkbox"/>
Test class, type 3	<input checked="" type="checkbox"/>
Protection rating	IP 20
Protection rating	IP20
Protection level	<1,5 kV
Protection level (N-PE)	< 1,5 kV
Protection level (L-N)	< 1,2 kV
Protection level (L-N / L/N-PE)	<1200 / <1500 V
Signalling on device	Visual
Temperature range	-25°C+75°C °C

Technical data sheet

FineController FC-B for sockets B/F

Item no. 5092840



Technical data

