### **Technical data sheet**

# **UDHOME-ONE** floor socket, with floor covering recess, BS socket, brass

**Item number: 7368310** 





Square floor socket for use in dry-care systems and screed floors in indoor areas. Installation housing with pre-marked insertion openings for pipes (M20/M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 85 mm, the height adjustment range +20 mm. Frame and cover made of brass and visible in the floor covering. Cover with floor covering recess. The load-bearing capacity of 15 kN is only guaranteed when in an unused state. The delivery includes a switched BS socket.





Brass

#### Master data

| Item number                            | 7368310                      |
|--|------------------------------|
| Туре                                   | UDHOME-ONE M15BS             |
| Description 1                          | Floor socket                 |
| Description 2                          | BS socket, 15mm floor recess |
| Manufacturer                           | OBO                          |
| Dimension                              | 140x140x85                   |
| Material                               | Brass                        |
| Smallest sales unit                    | 1                            |
| Unit of quantity                       | Piece                        |
| Weight                                 | 227 kg                       |
| Weight unit                            | kg/100 pc.                   |
| CO2 Footprint (GWP) Cradle-to-<br>Gate | 9,1944 kg COe / 1 Piece      |
|  |                              |

## **Technical data sheet**


# **UDHOME-ONE** floor socket, with floor covering recess, BS socket, brass

**Item number: 7368310** 



# Dimensions 9 9 8

| Length | 140 mm |
|--------|--------|
| Width  | 140 mm |
| Height | 85 mm  |



#### Technical data

| Number of sockets according to the British standard | 1                       |
|---|-------------------------|
| Cable outlet version                                | Swivellable cord outlet |
| Equipment   | Single BS socket        |
| Floor covering protection frame                     | no                      |
| Floor care  | Dry                     |
| Cover version                                       | Floor covering recess   |
| Seal installation option                            | no                      |
| Application when used                               | 6.101.1 Dry floor care  |
| Application when unused                             | 6.101.1 Dry floor care  |
| Floor height, max.                                  | 105 mm                  |
| Floor height, min.                                  | 85 mm                   |
| Suitable for raised floor installation              | yes                     |
| Suitable for screed-flush closed underfloor ducts   | no                      |
| Suitable for screed-covered underfloor ducts        | no                      |
| Suitable for cavity floor installation              | yes                     |
| Suitable for wet care                               | no                      |
| Suitable for underfloor ducts                       | no                      |
| Device support to accept mounting boxes             | no                      |
| With floor covering recess                          | yes                     |
| Protection rating (IP) when used                    | IP20                    |
| Protection rating (IP) when unused                  | IP40                    |
| Protection rating IK code                           | IK10                    |
| Heavy-duty version                                  | no                      |
|   | •                       |

## **Technical data sheet**

**UDHOME-ONE** floor socket, with floor covering recess, BS socket, brass





| Technical data            |             |
|---------------------------|-------------|
| Vertical load, large area | to 15,000 N |
| Vertical load, small area | to 3,000 N  |
| Opening mechanism         | Handle      |
| Floor covering thickness  | 15 mm       |