

Technical data sheet

CombiController V25B, plug-in arrester 280 V

Item number: 5097055



Combination arrester – type 1+2

- Plug-in arrester can be separated from base without tools and current cut-off in base
- Including thermal and dynamic cut-off unit and visual fault display
- High current conductivity and long service life



Master data

Item number	5097055
Type	V25B 0 SO-280
Description 1	CombiController V25
Description 2	plug-in arrester
Manufacturer	OBO
Dimension	280V
Smallest sales unit	30
Unit of quantity	Piece
Weight	9.5 kg
Weight unit	kg/100 pc.


Technical data sheet

CombiController V25B, plug-in arrester 280 V

Item number: 5097055



Technical data



Response time	<25 ns
Blow-out	no
Version for	1-pole
Pole version	1
Structural width in division units (division unit, 17.5 mm)	1
Operating temperature, max.	80 °C
Operating temperature, min.	-40 °C
Lightning surge current (10/350 µs)	25 kA
Maximum continuous voltage AC	280
Conductor cross-section, rigid (single-wire/multiwire), max.	35 mm ²
Conductor cross-section, rigid (single-wire/multiwire), min.	2.5 mm ²
Lightning protection zone LPZ	0→2
Max. mains-side overcurrent protection	160
Maximum back-up fuse	160 A
Nominal discharge current (8/20 µs)	30 kA
Nominal voltage AC (50/60 Hz)	230 V
Protection rating	IP20
Protection level	≤0,9
Signalling on device	Visual
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-1	Class I+II