Technical data sheet

Junction box X 16

Item number: 2005130





Junction box for the connection of cables and lines indoors and in outdoor areas. Rectangular design with knock-out entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Cover with quick lock, sealable. Made from halogen-free and UV-resistant materials. Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK09 according to DIN EN 50102. Protection rating IP67 according to DIN EN

























Polycarbonate

Master data

2005130
X16 SW
Junction box
OBO
240x191x125
Graphite black; RAL 9011
Polycarbonate
1
Piece
79.3 kg
kg/100 pc.
2,9477 kg COe / 1 Piece

Technical data sheet

191

Junction box X 16

Item number: 2005130



Dimensions Length Width 191 mm Height 126 mm

Technical data

241

Expandable	yes		
No. of entries	10		
Type of entry	Cuttable stepped membrane		
Type of housing penetration	Pre-marking		
Measured insulation voltage Vi	750 V		
Equipment	Without		
Cover	Not transparent		
Cover fastening	Screwed		
Entry from rear	no		
Entries	10 x Ø25/32/40		
Explosion-tested version	no		
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C		
Shape	Rectangular		
Fibre-glass reinforced	yes		
Halogen-free	yes		
Clear internal dimensions	227x177x110 mm		
Max. Conductor cross-section	16 mm²		
With screening	no		
with lid	yes		
Mounting type	Wall/ceiling mounting		
Nominal cross-section, max.	16 mm²		
Nominal cross-section, min.	6 mm ²		
Nominal voltage	750 V		
Sealable	yes		
Impact-resistant	yes		
Protection rating	IP67		
Protection rating IK code	IK09		
Permitted temperature range, max.	60 °C		
Permitted temperature range, min.	-5 °C		
Transparent lid	no		

Technical data sheet Junction box X 16



Item number: 2005130

Technical data		
	Weatherproof	yes