

Technical data sheet

PV surge protection V20, 1,000 V DC

Item number: 5094608



- V20 surge arrester, type 2, for photovoltaic systems
- Complete unit, consisting of plug-in varistor arrester with cut-off unit
 - Error-resistant Y circuit to VDE 0100-712 (EN 50539-12)
 - Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
 - V20-C 3-PH-1000 tested to EN 50539-11 (VDE / KEMA)
 - Arresting capacity to 40 kA (8/20) per pole
 - Low DC protection level: < 4.0 kV and Voc max = 1,000 V DC
 - With visual status display for use in distributor housings
- Application: PV systems with or without separate lightning protection system



Master data		
	Item number	5094608
	Type	V20-C 3-PH-1000
	Description 1	SurgeController V20
	Description 2	three-pole for photovoltaics
	Manufacturer	OBO
	Dimension	1000V DC
	Smallest sales unit	1
	Unit of quantity	Piece
	Weight	34.519 kg
	Weight unit	kg/100 pc.
	CO2 Footprint (GWP) Cradle-to-Gate	0,9504 kg CO2e / 1 Piece


Technical data sheet

PV surge protection V20, 1,000 V DC


Item number: 5094608



Dimensions



Technical data



Response time	<25 ns
Blow-out	no
Version for	3-pole for PV systems
Pole version	3
Structural width in division units (division unit, 17.5 mm)	3
Operating temperature, max.	80 °C
Operating temperature, min.	-40 °C
Remote signalling	no
Maximum continuous voltage DC	1000 V
Conductor cross-section, rigid (single-wire/multiwire), max.	35 mm ²
Conductor cross-section, rigid (single-wire/multiwire), min.	2.5 mm ²
Lightning protection zone LPZ	1→2
Max. mains-side overcurrent protection	125
Maximum back-up fuse	125 A
Maximum discharge current (8/20 µs)	40 kA
Installation type	DIN rail 35 mm
Nominal discharge current (8/20 µs)	20 kA
Network form	Other
DC network form	yes
Test class, type 2	yes
Protection rating	IP20
Protection level	≤4,0
Signalling on device	Visual
SPD to EN 61643-11	Type 2
SPD to IEC 61643-1	Class II
Permitted temperature range, max.	80 °C
Permitted temperature range, min.	-40 °C