

Technical data sheet

Fixed earthing terminal with connection bolt and double thread FT

Item number: 5420024



- For connecting to earthing systems, conductors and reinforcements
- Contact plate: Ø 79 mm from stainless steel, rustproof (V4A)
- With M10 and M12 thread
- Including plastic cover for easy installation
- With connection bolt Ø 10 mm (FT)



St Steel

FT Hot-dip galvanised

Master data	
Item number	5420024
Type	205 DG L180 FT
Description 1	Earthing fixed point with axis
Description 2	and double thread
Manufacturer	OBO
Dimension	M10/M12
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	10
Unit of quantity	Piece
Weight	23.9 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	1,2723 kg CO2e / 1 Piece


Technical data sheet

Fixed earthing terminal with connection bolt and double thread FT

Item number: 5420024



Dimensions



Length	180 mm
--------	--------

Technical data

Diameter of the connection bolt	10 mm
Lightning current carrying capacity	H/100 kA
Diameter of the contact plate	79 mm
Thread	M10/M12
Short-circuit current (50 Hz)(1 s; $\leq 300^{\circ}\text{C}$)	4.9 kA
Material of the connection bolt	Steel, hot galvanised