Technical data sheet


Cable tray, marine standard







Cable tray according to marine standard. The cable track is manufactured according to the VG standard 88900. The side rail of the cable track is unperforated.





Stainless steel, grade 316 Ti

Bright, reworked

Master data

Туре	MKR 15 250 A4
Manufacturer	OBO
Colour	Stainless steel
Material	Stainless steel, grade 316 Ti
Surface	Bright, reworked
Surface standard	
Smallest sales unit	2
Unit of quantity	Metres
Weight	235.25 kg
Weight unit	lbs/100 pcs.

Dimensions

Dimension	15 X 250
Length	2,000 mm
Width	250 mm
Height	15 mm
Plate thickness	1.5 mm
Dimension B	250 mm

Technical data sheet

Cable tray, marine standard



Item number: 6045862

Chalfant Item Nb.

Features/properties/dimensions		
	Connector version	Without connectors
	Walkable	no
	Maintain electrical functions	no
	With cover	no
	Mounting perforation in base	yes
	NATO hole pattern	yes
	Rustproof steel, pickled	yes
	Side perforation	no
	Wide-span version	no
	Load test type according to IEC 61537	Type II
Loads		
	Support spacing 1.0 m	0.75 kN/m
	Support spacing 1.5 m	0.25 kN/m