## **Technical data sheet**

#### FireBox T100 with plug-in seals, 2 fuse holders







Junction box with two fuse holders and soft plug-in seals. Sufficiently large wiring compartment through diagonally arranged connection unit with completely premounted, high-temperature-resistant ceramic terminals. Green-yellow labelled protective conductor terminal. Fastening on easily accessible external flaps. Approved for cable systems that maintain the electrical function according to DIN 4102 Part 12 with the classes E30, E60 and E90. Ceramic clamps have been tested according to DIN EN 60998-2-1:2004.

Including 2x MMSplus P 6x35 screw ties.









Polypropylene

#### Master data

Item number	7205758
Туре	T100ED 06A2F
Description 1	Junction box
Description 2	for function maintenance
Manufacturer	OBO
Dimension	150x116x67
Colour	Pastel orange; RAL 2003
Material	Polypropylene
Smallest sales unit	1
Unit of quantity	Piece
Weight	52.95 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	1,759 kg CO2e / 1 Piece

## **Technical data sheet**

# FireBox T100 with plug-in seals, 2 fuse holders



**Item number: 7205758** 

#### Dimensions Length Width 150 mm 116 mm Height 67 mm Dimension B 116 mm Dimension H 67 mm Dimension L 150 mm Dimension L1 162 mm OBO 1101 Dimension L2 182 mm 150 162

Tac	hni	Ca	21	2

182

Expandable	no
No. of entries	10
Number of terminals	7
Type of housing penetration	Cuttable stepped membrane
Measured insulation voltage Vi	690 V
Equipment	Teminal
Cover	Not transparent
Cover fastening	Screwed
Entry from rear	no
Entries	8x M25
	2x M32
Explosion-tested version	no
Shape	Rectangular
Maintain electrical functions	E 90
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Halogen-free	yes
Clear internal dimensions	136x102x57 mm
With screening	no
with lid	yes
Nominal cross-section, max.	6 mm²
Nominal cross-section, min.	1.5 mm <sup>2</sup>
Nominal voltage	660 V
Sealable	no
Impact-resistant	no
Protection rating	IP66
Transparent lid	no
Weatherproof	no