Technical data sheet Closed FireBox T100, empty







Unequipped, closed connection or junction box for free termination with ceramic terminals and cable glands. Dimension A states the available support rail length for the wiring terminals. Sufficiently large wiring compartment through diagonally arranged support rail. Fastening on easily accessible external flaps made of stainless steel. Approved for cable systems that maintain the electrical function according to DIN 4102 Part 12 with the classes E30, E60 and E90.











Polypropylene

Master data


Item number	7205780
Туре	T100E 0VA
Description 1	Junction box
Description 2	for function maintenance
Manufacturer	OBO
Dimension	150x116x67
Colour	Pastel orange; RAL 2003
Material	Polypropylene
Smallest sales unit	1
Unit of quantity	Piece
Weight	33.89 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	2,3617 kg CO2e / 1 Piece

Technical data sheet Closed FireBox T100, empty





Dimensions 69



150 mm
116 mm
67 mm
101 mm
116 mm
67 mm
150 mm
162 mm
182 mm

Technical data

Equipment	Support rail
Cover	Not transparent
Cover fastening	Screwed
Entry from rear	no
Maintain electrical functions	E 90
Halogen-free	yes
Clear internal dimensions	136x102x57 mm
With screening	no
with lid	yes
Nominal cross-section, max.	6 mm ²
Nominal cross-section, min.	0.5 mm²
Sealable	no
Protection rating	IP66