Technical data sheet

UDHOME-ONE floor socket, without floor covering recess, freely equippable, brass Item number: 7368284





Square floor socket for use in dry-care systems and screed floors in indoor areas. Installation housing with pre-marked insertion openings for pipes (M20/M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 75 mm, the height-adjustment range +30 mm. Frame and cover made of brass and visible in the floor covering. Cover with decorative plate. Empty housing for a 45® installation device and a data socket. When delivered, the item is closed with a blanking plate.





Brass

Master data

Item number	7368284
Туре	UDHOME-ONE GM
Description 1	Floor socket
Description 2	unequipped, brass decor lid
Manufacturer	OBO
Dimension	140x140x75
Material	Brass
Smallest sales unit	1
Unit of quantity	Piece
Weight	220 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	9,786 kg CO2e / 1 Piece

Technical data sheet


UDHOME-ONE floor socket, without floor covering recess, freely equippable, brass Item number: 7368284



Dimensions



•	140 mm
Width	140 mm
Height	75 mm



Technical data

2
Swivellable cord outlet
Empty housing
no
Dry
Decorative plate
no
6.101.1 Dry floor care
6.101.1 Dry floor care
105 mm
75 mm
yes
no
no
yes
no
no
no
no
IP20
IP40
IK10
no
to 15,000 N

Technical data sheet

UDHOME-ONE floor socket, without floor covering recess, freely equippable, brass Item number: 7368284



Technical data	
Vertical load, small area	to 3,000 N
Approvals	VDE
Opening mechanism	Handle