

Technical data sheet

33° socket, protective contact, triple

Item no. 6120132



Power socket Triple 33°, with increased touch protection with screwless terminals, 2-pin, 16 A, 250 V~, with connection terminals to IEC 60884-1.



PC

Polycarbonate

Additional product text 2

For installation in Rapid 45 ducts, device installation ducts, installation columns, underfloor systems and Deskboxes.

Master data

Item no.	6120132
Type	STD-D3 AL3
Description 1	Socket 33°, triple
Description 2	protective contact
Dimension	250V, 10/16A
Colour	Aluminium-painted
Material	Polycarbonate
Material symbol	PC
Smallest sales unit (VG)	1,00 Piece
Weight	11,00 kg/100 pc.

Technical data

	Width	135,00 mm
	Height	45,00 mm
	Depth	42,00 mm
	Cover	Central plate
	Closable	☐
	Connection type	Screwless terminal
	Printed label/coding	Without printing
	Version	Triple 33°
	Version	Socket 33°, triple, protective contact
	Surface version	Matt
	Sockets/switch version	SCHUKO
	Version for	SCHUKO
	Number of poles	2,00
	Number of units	3,00
	Number of modules (for modular construction)	0,00
	Number of switchable sockets	0,00
	Ejection mechanism	☐

Technical data sheet

33° socket, protective contact, triple

Item no. 6120132



Technical data

Fastening type	Lock
Labelling panel	☐
Operating temperature	-5,00 - 40,00 °C
Error current protection	☐
For more difficult conditions (according to VDE)	☐
Halogen-free	☒
Insulated installation	☐
Increased touch protection	☒
Hinged cover	☐
Coding	No
Warning light	☐
With on/off switch	☐
With fine-wire fuse	☐
With functional lighting	☐
With orientation lighting	☐
Mounting type	Device installation duct
Nominal voltage	250,00 V
Nominal current	16,00 A
Protection rating	Other
Special power supply	Without special power supply
Socket version	Schutzkontakt
Socket angle	33°
Transparent	☐
Surge protection	☐
Rotated central insert	☒