## **Technical data sheet**

Device installation trunking Rapid 80, trunking width 110, trunking height 90, symmetrical ltem no. 6277100

Steel






GS device installation trunking for mounting on the wall or on fastening panels. The GS device installation trunking possesses self-contacting locking straps to accept a sheet steel partition. The equipotential bonding between the trunking bases takes place using the trunking coupling. The protective measure and the equipotential bonding is guaranteed between the cover and the base by the self-contacting trunking cover. The real system opening is 76.5 mm. The cover must be ordered separately.

Over-lengths up to 3000 mm for trunking bases and covers as well as other RAL colours can be provided on request. The visible surfaces of the painted device installation trunking are laminated.

## Master data

Item no. 6277100 Type GS-S90110RW Description 1 Device installation trunking Description 2 symmetrical Dimension 90x110x2000 Pure white Colour RAL number 9010 Material Steel Material symbol St Smallest sales unit (VG) 2 m 290,00 kg/100 m Weight

## **Technical data**



Length	2.000,00 mm
Width	110,00 mm
Height	90,00 mm
Number of covers	1
Number of insertable partitions	1
Rear panel version (inner side)	With locking lugs
Rectangular shape	
Fastening type	Screw-on
Base perforation	with base perforation
Cable retaining clip	
Trunking height	90,00 mm
Trunking height	110,00 mm
Duct connector	
Cover mounting type	Internal
Mounting perforation in base	
Usable cross-section	83,00 cm <sup>2</sup>
Usable cross-section	8.300,00 mm <sup>2</sup>
Cover width	76,5 mm
Cover width 2	0,00 mm
Cover width 3	0,00 mm
Cover supplied	
Protective film	$\square$

## **Technical data sheet**

Device installation trunking Rapid 80, trunking width 110, trunking height 90, symmetrical Item no. 6277100



Technical data		
	Symmetrical	